



**CHARACTERISTICS**

- Water based tile cement
- Ready for use
- Excellent initial adhesion
- Water resistant after curing
- Solvent free

**APPLICATIONS**

- Bonding of ceramic tiles and natural stone (except for marble) on almost all types of walls, such as: cement binded materials, plaster binded materials, plate materials, wood, existing tiles...
- Very suitable for tiling in high humidity environments such as showers, kitchens and bathrooms.

TECHNICAL CHARACTERISTICS	
Base	Acrylic dispersion
Consistency	Paste
Vulcanisation	Evaporation of water
Application temperature	+5°C - +30°C
Open time	10 - 15 min
Drying time	min. 24 hours
Density	1,82 g/ml
Consumption	1 - 1,5 kg/m <sup>2</sup>
Shelf life, in the original packing in dry conditions between +5°C and +30°C.	Min. 12 months

PACKING
6 buckets of 1,5 kg/box - 40 boxes/pallet
Bucket 5 kg - 60 buckets/pallet
Bucket 10 kg - 30 buckets/pallet

**METHOD OF USE**

**Preparation**

All surfaces should be dry, degreased and clean. On porous surfaces, we recommend to treat the surface with a layer of glue.

**Application**

- Apply **Paracol Tile** with a glue comb (5 mm).
- Tiles should be applied within 10 minutes. Press to ensure a good bonding.

**Cleaning**

With water.

**SAFETY**

Safety data sheet available on request.

**TECHNICAL APPROVALS**



\* Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions).

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.