



CHARACTERISTICS

- Liquid, bituminous, fast-drying adhesive
- Due to the addition of bonding dopes can also be applied to a slightly moist surface
- Drying time : 3 to 4 hours
- Considerable improves adhesion between the base surface and the material to be applied

APPLICATIONS

- Adhesive layer for the application of roofing or bituminous renovation products
- The fixing of dusty and absorbent surfaces
- Protection of concrete, brickwork, etc.

TECHNICAL CHARACTERISTICS	
Base	Bitumen, adhesive additives and solvent.
Colour	Black
Consistency	Thin liquid, great penetrating capacity
Drying time	3 - 4 h depending on ambient conditions.
Solvents	Petroleum hydrocarbons - with use take necessary elementary precautionary measures. After use, Paraphalt Primer is considered as not fire dangerous according to TNO.
Flash point cc (astm d93)	40°C
Visco 40 C (astm d445)	46,93 mm ² /s
Density	0,93
Application temperature	-5°C - +30°C
Theoretic consumption	Between 5 and 6 m ² /l depending on the porosity of the surface to be treated
Shelf life, in unopened packing.	Min. 18 months

PACKING
Can 5 kg - 96 cans/pallet
Can 10 kg - 44 cans/pallet

METHOD OF USE

Application

- Apply with a brush, rubber squeegee or airless on clean dust- and grease-free surface

Cleaning

Clean tools with white-spirit

SAFETY

Safety data sheet available on request.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.