



**CHARACTERISTICS**

- Cleansing product
- Solvent based

**APPLICATIONS**

- Can be used to remove the following dirt: asphalt marks, grease marks and all persistent dirt
- For removing dirt
- And for preventing the formation of spots
- On white rigid PVC and other synthetic material
- Including lacquered surfaces.

<b>TECHNICAL CHARACTERISTICS</b>	
Physical state (20°C)	Liquid
Colour	Colourless
Odour	Characteristic
Boiling interval	63-100°C
Flash point	60°C – 62°C
Density (15°C)	0,7 kg/l
Auto ignition temperature	> 200°C
Shelf life, in the original packing in dry conditions between +5°C - +25°C	2 years

<b>PACKING</b>
12 spray cans of 400 ml/box - 60 boxes/pallet
Jar 5 l - 120 jars/pallet
Jar 25 l - 26 jars/pallet

**METHOD OF USE**

**Application**

We recommend, before use, to check if the product is convenient for its application and to do some preliminary tests.  
Aerosol 400 ml

- Shake can well before use
- Spray on the surface from a distance
- Remove dirt by means of a cloth. Then polish with a clean and dry cloth

Cannister 5 l & 25 l

- Remove dirt by means of a cloth soaked with **PVC Cleaner Soft**
- Then polish with a clean and dry cloth

**SAFETY**

Safety data sheet available on request.

**LIMITATIONS**

Not appropriate for rust spots

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.